



# THERMAL INSULATED SHUTTERS

Name:

Telephone:

Address:

Email:

Postcode:

Date:

Step 1	Step 2	Step 3		Step 4			Step 5	Step 6				Step 7
Room	Face or Reveal Fix	Dimensions (mm) Refer to notes on Fix below		Room-side Finish			Type	N. of Panels				Opening Hinge Arrangement
		Width	Height	White	Grey	Tan	Solid/Glass	1	2	3	4	Refer to Hinge Notes Below

Frame Types [3]: The 3-sided frame is for Left, Right, Top for Inside of the Reveal or the Face Outside Reveal Fixing.

Allows Window Boards to remain clear and does not obstruct any inward open window sashes, such as Tilt N' Turn Windows or Pivot Windows, if face mounted.

**Notes on Fix:**

- **Face-Fix:** Shutters are mounted on the outside of the window frame or wall. Dimensions to be calculated as the **Inside Reveal Dimensions +92mm in width and +46mm in height.**
- **Reveal-Fix:** Shutters are mounted inside the window recess. Dimensions to be calculated as the **Inside Reveal Dimensions -6mm in width and -3mm in height.**
- **Manufacturing sizes** to be supplied by customer

Overall Shutter Frame Width		
	Min (min)	Max (min)
Single	504	786
Double	926	1488
Triple	1348	2190
Quadruple	1770	2600

**Hinge Notes:** 'H' denotes which side has the hinges for primary opening of the shutters/shutters

Example: *Single Sash:* HL/HR; *Double Sash:* : HLL/HLR/LHR/HRR; *Triple Sash:* HL RR/LL HR; *Quadruple Sash:* HLL RR/LL HRR